

Dialog-2-Cl

Versatile meter, 2-channel version for double chlorine measurements
(also available for oxygen, chlorine dioxide, ozone and hydrogen peroxide)



Kuntze Instruments
Instrumentation for Water
and Waste Water Analysis
3316 Leechburg Road
Lower Burrell, PA 15068
Tel: 724-339-8510
kuntze01@comcast.net
www.kuntze-instr.com

Description

Microprocessor-controlled 2-channel meter with standard front dimensions 96 x 96 mm (¼ DIN) for mounting in control panels, designed for water analysis applications. Two inputs to connect two chlorine sensors, i. e. open or membrane-covered potentiostatic 3-electrode sensors with or without Pt 100; simple 2-electrode sensors can also be used.

DIALOG AA is also available for measurements of dissolved oxygen, chlorine (free and total), chlorine dioxide, ozone, or hydrogen peroxide.

Main applications

- Waste water treatment
- Water purification
- Potable water
- Metal finishing industry
- Chemical industry
- Food & Beverage Industry

Features

- Plastic enclosure with standard dimensions 96 x 96 mm (¼ DIN)
- Pluggable terminals for easy installation
- Large illuminated LCD screen capable of alphanumeric and graphical presentation of measured value and customer programmed data
- Easy user-guided operation with only eight keys
- Password function preventing unauthorized access
- 2 integrated potentiostats for measurement of chlorine (or any other of the substances listed above)
- Double measurement
- 2 outputs configurable for channel 1, channel 2, temperature measurement, or as continuous controller output
- 4 inputs configurable for channel 1, channel 2, temperature 1, temperature 2, or for variable disturbance
- Temperature compensation either manually or via Pt-100
- Galvanically isolated inputs and outputs



Dialog-2-Cl

Versatile meter, 2-channel version for double chlorine measurements
(also available for oxygen, chlorine dioxide, ozone and hydrogen peroxide)



Kuntze Instruments
Instrumentation for Water
and Waste Water Analysis
3316 Leechburg Road
Lower Burrell, PA 15068
Tel: 724-339-8510
kuntze01@comcast.net
www.kuntze-instr.com

Controller (Option)

- 2 set points and alarm relays, freely configurable
- On/off controller with adjustable hysteresis
- PID controller (pulse-pause or pulse-frequency controller)
- PID 3-point controller
- Second output configurable as continuous controller output
- Variable disturbance implementable (0/4 – 20 mA)
- Indication of set point relay status in the display
- Manual operation of set points
- Adjustable onset delay
- Controller stop via external contact

Additional options

- Additional serial interface RS-485
- Power supply 24 VDC

Technical data

Power:	24 or 130 or 230 VAC, + 6 %, - 10 %, 40 ... 60 Hz
Optional	24 VDC
Power consumption:	10 VA
Ambient temperature:	operation 0 - 50 °C storage - 20 - 65 °C
Humidity, % rF: (non-condensing)	max. 90 % at 40 °C
Enclosure:	plastic enclosure 96 x 96 x 125 mm (¼ DIN) for mounting In control panels protection class IP-54 (front), IP-30 (enclosure)
Weight: 0.8	kg
Connectors: pluggable	terminals
Analogue inputs:	4 inputs, two of them high impedances, configurable for channel 1, channel 2, temperature 1, temperature 2, or for variable disturbance (with controller option)
Measuring ranges:	0.00 ... 5.00 mg/l chlorine / -30 - 140 °C Or 0.00 ... 5.00 mg/l chlorine dioxide Or 0.00 ... 2.00 mg/l ozone Or 5 ... 100 mg/l hydrogen peroxide measuring ranges available
other	
Accuracy:	+/- 1 % of the upper limit or +/- 0.05 mg/l/ +/- 0.1 °C
Analogue outputs:	2 outputs 0/4 - 20 mA, galvanically isolated, configurable for measured value 1, measured value 2, temperature measurement, or as continuous control output
Registration ranges:	adjustable within measuring ranges
Load: max.	400 Ohm
Interface:	RS 485 / second interface optional
Electromagn. compatibility:	according to DIN EN 50081-1 and 50081-2
In compliance with:	CE

Dialog-2-CI

Versatile meter, 2-channel version for double chlorine measurements
(also available for oxygen, chlorine dioxide, ozone and hydrogen peroxide)



Kuntze Instruments
Instrumentation for Water
and Waste Water Analysis
3316 Leechburg Road
Lower Burrell, PA 15068
Tel: 724-339-8510
kuntze01@comcast.net
www.kuntze-instr.com

Controller (Option)

to control solenoid valves, actuators or feeding pumps,
2 set points (freely configurable) and alarm

Control functions:	on/off controller with adjustable hysteresis PID controller (pulse-pause or pulse-frequency controller Or continuous controller output 0/4 – 20 mA)
Disturbance variable:	0/4 – 20 mA
Manual operation:	manual operation of set points possible
Alarm delay:	adjustable (0 – 1999 s)
Relays outputs:	3 relays outputs for SP 1, SP 2, alarm, each with 1 NO/NC contact (SPDT) max. 250 V, 6 A, 550 VA;
Digital input	indication of set point relay status in the display external contact hold (controller stop)

Order numbers:

DIALOG PP with enclosure 96 x 96 mm, without controller	7655441
DIALOG PP with enclosure 96 x 96 mm, with integrated controller	7655445
Optional second interface RS-485	7611453

If supply voltage differs from 130 V, please indicate.